



定格荷重表

	R-25m	R-30m	R-35m
3m	11.00	10.00	8.00
	↓	↓	↓
14m			8.00
15m	11.00	10.00	7.50
16m	9.90	9.00	7.00
17m	9.00	8.20	6.50
18m	8.20	7.60	6.20
19m	7.60	7.10	5.80
20m	7.10	6.70	5.50
21m	6.70	6.30	5.20
22m	6.30	5.90	5.00
23m	5.90	5.60	4.70
24m	5.60	5.30	4.50
25m	5.30	5.00	4.30
26m		4.80	4.10
27m		4.50	3.90
28m		4.40	3.80
29m		4.20	3.60
30m		4.00	3.50
31m			3.40
32m			3.30
33m			3.20
34m			3.10
35m			3.00

仕様

ジブ呼び		25m	30m	35m
速度	巻上	(m/min)	24~100[11~0t]	
	起伏	(s)	111	
	旋回	(rpm)	0.42[R-35m 7.0t以上時 0.25rpm]	
	走行	(m/min)	7.9	
電源		400V 50Hz(440V 60Hz)		
電動機	巻上	55kW 4P 60%ED インバータ制御		
	起伏	15kW 4P CONT インバータ制御		
	旋回	7.7kW 4P CONT インバータ制御		
	走行	2×3.7kW 4P 75%ED		
最大設置高さ	(m)	320	170	150